

AMENDMENTS TO THE CLAIMS

1-17. (Canceled)

18. (Currently Amended) A guidance display device which holds a first display region and a second display region, and a guidance display region for displaying a guidance content, ~~said~~ the guidance display device comprising:

a first guidance display unit configured to display first display data in the first display region;

a second guidance display unit configured to display second display data in the second display region; and

a third guidance display unit configured to display, in the guidance display region, a synthesized or combined guidance content which is synthesized or combined from a first guidance content for operating the first display data currently being displayed in the first display region and a second guidance content for operating the second display data currently being displayed in the second display region,

wherein the guidance display region is separate from the first and second display regions, and

said third guidance display unit is configured to display the synthesized or combined guidance content in the guidance display region when the first and second display data are being displayed.

19. (Currently Amended) The guidance display device according to Claim 18, further ~~comprising~~ comprising:

a guidance contents holding unit configured to hold the first guidance and the second guidance contents,

wherein said third guidance display unit is configured to synthesize, into the synthesized guidance, the first guidance content and the second guidance content which have been obtained from said guidance contents holding unit according to an obtainment order indicating an order of obtaining the first guidance content and the second guidance content.

20. **(Currently Amended)** The guidance display device according to ~~Claim 19~~Claim 19, further comprising:
- a determination unit; and
 - a third display region including the first and the second display regions,
- wherein said guidance contents holding unit is further configured to hold a third guidance content that is a guidance for operating the first and the second display data, the third guidance content corresponding to the third display region,
- said determination unit is configured to determine whether or not the first or the second display data is to be operated, and
- said third guidance display unit is configured to display, in the guidance display region, a guidance synthesized from the first guidance content and the third guidance content when said determination unit determines that the first display data is to be operated.
21. **(Previously Presented)** The guidance display device according to Claim 20,
- wherein, in the case of change in a facing direction of said guidance display device, said guidance display device changes an arrangement of at least one of the first display region, the second display region, and the guidance display region, and to display, in the guidance display region, the synthesized guidance content obtained by combining plural guidance contents corresponding to the first and the second display regions which are rearranged as a result of the change in the arrangement.
22. **(Previously Presented)** The guidance display device according to Claim 21,
- wherein the change in the facing direction is turning said guidance display device or folding said guidance display device.
23. **(Previously Presented)** The guidance display device according to Claim 22,
- wherein turning said guidance display device is turning said guidance display device approximately 180 degrees.

24. **(Currently Amended)** A guidance display method for use in a guidance display device which holds a first display region and a second display region, and a guidance display region for displaying a guidance, ~~said the~~ guidance display method comprising:

displaying first display data in the first display region;

displaying second display data in the second display region; and

displaying, in the guidance display region, a synthesized or combined guidance content which is synthesized or combined from a first guidance content for operating the first display data currently being displayed in the first display region and a second guidance content for operating the second display data currently being displayed in the second display region,

wherein the guidance display region is separate from the first and second display regions, and

the synthesized or combined guidance content is displayed in the guidance display region when the first and second display data are being displayed.